

iNFINITI 7000 Series Satellite Router

Delivering Highly Secure, Reliable and Fast IP Broadband Connectivity

Developed to meet the most demanding user requirements for security and performance, the 7000 series satellite router is ideal for high-speed two-way IP traffic supporting the communications, command, and control requirements of today's highly mobile military forces and government agencies.

The iNFINITI 7000 Series uses the high performance TDM on the outbound and highly efficient deterministic MF-TDMA technology on the inbound, delivering speeds up to 20 Mbps on the outbound and up to 7.7 Mbps on the inbound. Supporting multiple topologies such as star, mesh, and star/mesh networks as well as point-to-point iSCPC enable maximum flexibility when it comes to the integration of a variety of applications into a single platform.

High Security

Compliant with the highest military security requirements the 7000 Series features embedded AES encryption and TRANSEC with advanced FIPS 140-2 certification, X.509 digital certificate encryption, and automatic over the air key exchange.

Superior Quality of Service

Flexible Quality of Service and prioritization capabilities enable network operators to not only prioritize traffic and applications over their networks but with iDirect's state-of-the-art Group QoS they can segregate bandwidth by groups of remotes, by multiple sub-networks, and by multiple mission-critical applications.

Increased Bandwidth Efficiencies and Network Availability

Supporting a wide variety of the most advanced turbo product codes (TPC) FECs, the 7000 Series remote offers efficient error correction code techniques and provides a greater flexibility for network design and optimization. Furthermore, iDirect's patented, deterministic MF-TDMA highly maximizes inbound throughput. Increased network availability is also achieved with built-in automatic end-to-end uplink power control providing effective, automatic, and safe power management to compensate for uplink rain and atmospheric attenuation.

Simple Network Management

Operating with all iDirect hubs, the 7000 Series remotes can be easily configured, monitored, and controlled through the iVantage™ Network Management System. This easy-to-operate and very intuitive NMS has been the industry's most renowned and robust network management system, proven and perfected for nearly a decade.



Features

- ◆ Multiple topologies: Star, Mesh, iSCPC
- ◆ High data rates of up to 20 Mbps outbound, 7.7 Mbps inbound
- ◆ Efficient multifrequency, deterministic TDMA
- ◆ Advanced QoS and prioritization
- ◆ Unique FIPS 140-2 certified, TRANSEC security with AES encryption
- ◆ Built-in 8-port Ethernet switch
- ◆ Optional +48 VDC output supporting higher BUC power

iNFINITI 7000 Series Satellite Router Model 7350



Network Configuration

Network Topology	Star, iSCPC and Mesh	
	<u>Downstream (iNFINITI TDM)</u>	<u>Upstream (D- TDMA)</u>
Modulation	BPSK, QPSK, 8PSK	BPSK, QPSK
FEC	Turbo, 0.495 - 0.879	Turbo, 0.431 - 0.793
Maximum Rates	Symbol	7.5 Msps
	Info	11.8 Mbps
	Carrier IP Data	10.8 Mbps
	Remote IP Data	7.7 Mbps
	Notes:	QPSK, .879 FEC
		QPSK, .793 FEC
	<i>Maximum downstream and upstream data rates cannot be achieved simultaneously Maximum rates are achieved under optimal conditions and with unlimited NMS</i>	
E_b/N₀	For full list, please refer to the latest iDirect Link Budget Analysis Guide	

Interfaces

SatCom Interfaces	TxIF: Type-F, 950–1700 MHz, Composite Power +7dBm / -35dBm RxIF: Type-F, 950–1700 MHz, Composite Power -5dBm / -65dBm TVRO: Type-F, 950–1700 MHz
Available BUC Power (IFL)	+24V or +48V (Optional +48V supports up to 16W Ku-band or 20W C-band)
Available LNB Power (IFL)	+19.5V (Nominal)
10 MHz Reference	Software controllable on Tx and Rx IF ports
Data Interfaces	LAN: Single 10/100 and 8-Port 10/100 Switch, 802.1q VLAN RS-232: RJ45 (for GPS or Console connection or Antenna Pointing)
Protocols Supported	TCP, UDP, ACL, ICMP, IGMP, RIP Ver2, BGP, Static Routes, NAT, DHCP, DHCP Helper, Local DNS Caching, cRTP and GRE
Security	AES Link Encryption (256-bit), TRANSEC with FIPS 140-2 certification, x.509 digital certificates authentication, Automatic Key Management
Traffic Engineering	Group QoS, QoS (Priority Queuing and CBWFQ), Strict Priority Queuing, Application Based QoS, Minimum CIR, CIR (Static and Dynamic), Rate Limiting
Other Features	Built-in Automatic Uplink Power, Frequency and Timing Control, Authentication, Antenna Control Interface (OpenAMIP)

Mechanical/Environmental

Size	W 17.5 in x D16.0 in x H1.75 in (W 44.45 cm x D 40.6 cm x H 4.4 cm)
Weight	11.2lbs (5.1 Kg)
Operating Temperature	0° to 50°C (+32° to +122°F) at Sea Level with temperature gradient of 1°C per 1 min 0° to 45°C (+32° to +113°F) at 10000 Feet with temperature gradient of 1°C per 1 min For ODU power consumption <70W (please refer to iNFINITI 7000 Installation Manual for details)
Humidity	Max 90% non-condensing humidity
Input Voltage	100–240 VAC Universal Input, 50–60 Hz, 4A max at 90 VAC, 2A max at 240 VAC
Radio Standards	EN 301-428 v1.3.1 — Ku-Band System Level Specification EN 301-443 v1.3.1 — C-Band System Level Specification
Safety Standards	Complies with IEC 60950, EN 60950-1, UL 60950-1, CSA C22.2 No.60950-1-03
Emission Standard	Complies with EN 55022 Class B, FCC Part 15 Class B, CISPR 22 Class B, EN 61000-3-2, EN 61000-3-3
EMC/Immunity Standard	Complies with EN 55024, EN 301-489-1, EN 301-489-12, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-11
Certification	FCC, CE and RoHS compliant